

Extensometer



FEATURES

- Strain gage based sensor
- Alloy steel construction
- 2 bolt holes
- IP67 Hermetically sealed protection

OPTIONAL FEATURE

- Redundant sensor (model 176)
- Digital output (LIN-Bus)

DESCRIPTION

The 174 extensometer is a sensor used for safety applications in lifting devices.

This product is used widely in many lifting machines, telescopic loaders and any other moment sensitive lifting device.

The 174 extensometer is a strain gage based sensor. It can be supplied with analog or digital output.

The digital version is supplied widely as set


together with the model LMI521 display.

The 174 extensometer is usually installed on the rear side of the device and it measures the load decrease on the rear shaft.

APPLICATIONS

- Lifting machines
- Telescopic loaders

OUTLINE DIMENSIONS in millimeters



Extensometer

SPECIFICATIONS		
PARAMETER	VALUE	UNIT
Calibrated output	1.0	mV/V at 500 $\mu\epsilon$
Overload capability (zero)	300	% of rated output
Overload capability (max)	500	% of rated output
Input resistance	385 \pm 10	Ω
Output resistance	350 \pm 10	Ω
Insulation resistance	>2000	M Ω
Excitation, recommended	10	Vdc
Excitations, range	5-20	Vdc
Thermal effect on zero	0.025	\pm % of FSO/ $^{\circ}$ C
Compensated temperature range	-30 to +80	$^{\circ}$ C
Construction	Painted steel	
Environmental protection	IP67	



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.