

Weight Indicator

FEATURES

- Economical general-purpose weighing indicator
- Large 6 digit LED display
- Two serial ports for simultaneous printer and PC connection
- Heavy duty ABS enclosure
- Sample rate up to 30 conversions per second
- OIML R-76 and NTEP approved to 10000d
- 3 level digital filtering
- Programmable ticket format up to 185 characters
- Consecutive transaction numbering
- **Optional**
 - UL power adaptor
 - TUV power adapter
 - UK power adapter
 - High tilt stand
 - Low tilt stand

APPLICATIONS

- Shipping and receiving scales
- Floor scales
- Bench scales

NOT AVAILABLE IN THE FOLLOWING REGIONS:

- North America, Central America, South America



DESCRIPTION

The VT 100 is an economical general purpose weighing indicator for platform scales and other industrial applications.

Two serial ports, RS-232 and current loop, provide simultaneously PC and printer interface capability. Ticket formats may be edited and downloaded with programmable ticket numbering, date, and time.

Load cells are connected using a quick disconnect plug, allowing simple installation and maintenance.

The heavy duty ABS enclosure easily adjusts for desktop, wall (tilt), or post mounting.

CONFIGURATION



Weight Indicator

SPECIFICATIONS

PERFORMANCE

Resolution

10000 or 100000 dd (selectable)

Conversion Speed

3, 7, 15, or 30 samples (selectable)

Sensitivity1.0 $\mu\text{V}/\text{Vsi}$ for approved scales,
0.5 $\mu\text{V}/\text{Vsi}$ for non-approved scales**Full Scale Range**

3 mV/V

Linearity

0.01% of full scale

Long-Term Stability

0.005% of full scale per year

Excitation

+5 VDC with sense (6 wires)

Number of CellsUp to 8, 350 Ω load cells**Filter**

Digital filter - 3 stages

Offset Drift3.5 ppm/ $^{\circ}\text{C}$ **Span Drift**3.5 ppm/ $^{\circ}\text{C}$ **A/D Converter Type**

Sigma-Delta, ratiometric

Count By

x1, x2, x5, x10, x50

Decimal Point

Between any digits of the weight display

Calibration Methods

Dead load and span, store in EEPROM

Weighing Functions

Automatic zero tracking, motion detection, auto-zero on power-up, zero, tare, gross/net, print, units conversion

ENVIRONMENTAL

Operating Temperature-10 $^{\circ}\text{C}$ to +40 $^{\circ}\text{C}$ [14 $^{\circ}\text{F}$ to 104 $^{\circ}\text{F}$]**Storage Temperature**-10 $^{\circ}\text{C}$ to +70 $^{\circ}\text{C}$ [-4 $^{\circ}\text{F}$ to 158 $^{\circ}\text{F}$]**Relative Humidity**

40–90% RH, non-condensing

DISPLAY AND KEYBOARD

Display

6 digit, 7-segment, LED, 20.3 mm

Status Enunciators

No motion, zero, net, units (kg, g)

Weight Digits

4, 5 or 6 (setup selectable)

Keyboard

5 key membrane keyboard, with tactile feedback

ELECTRICAL

Voltage

9 VDC or 115 or 230 VAC using power adapter

Power

8W

SERIAL COMMUNICATION

Serial Output #1

RS-232

Baud Rate

1200–38400 baud, full duplex

Applications

Continuous or printer output, PC interface

Serial Output #2

20 mA current loop–output only

Baud Rate

1200–9600 baud

Applications

Printer port

ENCLOSURE—HEAVY GAGE ABS

Dimensions186.3 x 103 x 95 mm L x H x D
[7.32 x 4.05 x 3.74 in. L x H x D]**Mounting**

Desktop, wall and tilt mount

APPROVALS (ACCURACY CLASS III)

OIML R-76

10000d EU-type approval no. T6877

NTEP

10000d single interval

VPG Transducers is continually seeking to improve product quality and performance. Specifications may change accordingly.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.